



# LED 24V CV Driver

60W

PioLED Lighting (Pty) Ltd  
031 701 5746  
info@pioledlighting.africa

## Product Performance

<b>Wattage</b>	60W
<b>Colour Temperature &amp; Stock Code</b>	<b>PS002a</b>
<b>Operating Temperature</b>	-10 ~ 50°C
<b>IP Rating</b>	IP20
<b>Input Voltage</b>	185-265V
<b>Surge Protection</b>	1kV
<b>Dimmable</b>	No

## Physical Characteristics

<b>Weight (g)</b>	150
<b>Housing Material</b>	Pure Aluminium
<b>Product Dimensions (mm)</b>	H 170 x L 35x W 23
<b>Mounting Option</b>	-

## Technical Parameters

<b>Input Current</b>	0.52A
<b>Output Voltage</b>	24V
<b>Humidity</b>	20 ~ 99%RH, non- condensing
<b>Frequency</b>	50/60Hz
<b>In Rush Current</b>	Cold start 50A
<b>Output Current</b>	Max 2.5A
<b>THD</b>	≤1%
<b>TA &amp; TC</b>	ta: -45°C to: 85°C
<b>IES (Yes or No)</b>	No

## Regulatory Qualifications

<b>Energy Efficiency</b>	A
<b>Certification</b>	CE, EMC, IEC61347

## Packaging info

<b>Storage Temp</b>	-40°C ~ 80°C
<b>Carton Size (mm)</b>	37*29*22
<b>QTY/CTN</b>	100
<b>Net Weight</b>	14.5KG
<b>Gross Weight</b>	15.5KG

E&OE

PioLED Lighting (Pty) Ltd | 031 701 5746 | info@pioledlighting.africa

www.pioledlighting.co.za