



LED 24V CV Driver

120W

PioLED Lighting (Pty) Ltd
031 701 5746
info@pioledlighting.africa

Product Performance

Wattage	120W (5 Amp)
Colour Temperature & Stock Code	PS004a
Operating Temperature	-30 ~ 50°C
IP Rating	IP20
Input Voltage	175-264V
Surge Protection	1kV
Dimmable	Yes

Physical Characteristics

Weight (g)	320
Housing Material	Pure Aluminium
Product Dimensions (mm)	H 175 x L 48x W 29
Mounting Option	-

Technical Parameters

Input Current	1.32A
Output Voltage	24V
Humidity	20 ~ 99%RH, non- condensing
Frequency	50/60Hz
In Rush Current	Cold start 55A
Output Current	Max 5A
THD	≤1%
TA & TC	ta: -45°C tc: 85°C
IES (Yes or No)	No

Regulatory Qualifications

Energy Efficiency	A
Certification	IEC, CE

Packaging info

Storage Temp	-40°C ~ 80°C
Carton Size (mm)	53*21*24.5
QTY/CTN	60
Net Weight	17,2KG
Gross Weight	18,2KG

E&OE

PioLED Lighting (Pty) Ltd | 031 701 5746 | info@pioledlighting.africa

www.pioledlighting.co.za