



Bolts and Screws

Urban Back-lit LED Panels





Applications:

Residential and Commercial Applications.


acklit LED Panels have a durable yet minimal design which allows for easy installations in dropin ceilings or surface mount applications. The LEDs are situated on the back plate of the panel alleviating excess light guides allowing for a more cost effective LED Lighting Solution.

Our Backlit LED Technology evenly diffuses its SMD LED chips without creating dark spots with no risk of discoloration. Dimmable/Dali options available.

Product Performance	
Wattage	36W
Colour Temperature & Stock Code	3CCT (4000K_5000K_6000K) - iB121
Operating Temperature	-20~40°C
Life Span/ LB Rating	L80B10@50 000hrs
IP Rating	IP40
LED Driver	PioLED Driver
Beam Angle	120°
Impact Protection Grade	-
Input Voltage	180V-277V
Surge Protection	1.5kV
Power Factor	0.9
CRI	>80
Lumen Output	5 400 Lumens
Lumen Efficiency	150
LED Chips	2835 SMD
LED Chips Qty	192
LED Chip Brand	Sanan
Dimmable	Yes with 26-40W Driver - Dali Dim - iB101DA
Dimmable Range	-
(Dali/Trailing/Leading)	-
UGR	>19
Physical Characteristics	
Weight (g)	3200
Housing Material	Aluminium & Iron
Product Dimensions (mm)	1195*595*32
Cable Length	15cm
Mounting Option	Surface/Hanging/Recessed
Bracket Material	-

Stainless Steel

Packaging



Dimension Drawing



Technical Parameters	
Input Current	<350mA
Output Voltage	27-42V
Humidity	80%
Frequency	50-60Hz
In Rush Current	-
Output Current	950mA
THD	<15%
TA & TC	45/90
Flicker (Y/N)	No Flicker
IES (Yes or No)	Yes
Regulatory Qualifications	
Class Rating	Class II
Energy Efficiency	A
Certification	IEC60598, TUV, CE, EMC, LVD, SAA, RoHS, SO9001
Accessories	
Optional accessories	36W 6x12 Urban back-lit no flicker driver 5Y 125-65 - iB121PS 6x12 Back-Lit H65 Surface Mount Case - iB612 6x12 hanging kit - 1M x 6 - i6121 Extra 2Meter SS x 1 - i600 5Amp-3meter - R111 5Amp-2meter - R113
Packaging info	
Storage Temp	-20~80°C
Carton Size (mm)	1215*215*620
QTY/CTN	6
Net Weight	9.5
Gross Weight	10.85



Urban Back-lit Accessories




600x1200 Hanging Kit

36W 6x12 Urban back-lit Flicker Free 5 Year driver



Dali Dimmable Driver





Surface Mount Case



