



From Batch  
2411 All Oober  
Floodlights come  
with a Stainless  
Steel Bracket



# Oober IP65 Floodlight

## 10W

### Applications:

Residential and  
Commercial Applications.

- Die-Cast Aluminium housing with dynamic fins providing as an efficient and effective heatsink.
- Driver on Board Technology allowing for a super compact, unobtrusive LED Floodlight.
- 50cm pre wired cable allowing for fast and easy installations.
- Pre-Installed Safety Clips protecting the LED Floodlights lens.
- 2835 Sanán LED Chips producing a CRI>83.
- 120° Wide Beam Angle allowing for maximum coverage and uniformity.
- 3kV Surge protection, designed for use specifically in the South African Market.

### Product Performance

<b>Wattage</b>	10W
<b>Colour Temperature &amp; Stock Code</b>	6000K <b>F350</b>
<b>Operating Temperature</b>	-30~45°C
<b>Life Span/ LB Rating</b>	25 000hrs
<b>IP Rating</b>	IP65
<b>LED Driver Brand</b>	DOB
<b>Beam Angle</b>	120°
<b>Impact Protection Grade</b>	IK06
<b>Input Voltage</b>	200V- 260V
<b>Surge Protection</b>	3kV
<b>Power Factor</b>	0.9
<b>CRI</b>	>83
<b>Lumen Output</b>	900 lumens
<b>Lumen Efficiency</b>	90lm/W
<b>LED Chips</b>	2835 Sanan
<b>LED Chips Qty</b>	15
<b>Dimmable</b>	Non-Dimmable
<b>Dimmable Range</b>	-
<b>UGR</b>	-
<b>(Dali/Trailing/Leading)</b>	-

### Physical Characteristics

<b>Weight (g)</b>	185
<b>Housing Material</b>	Die cast Aluminium
<b>Product Dimensions (mm)</b>	78*68*32
<b>Cable Length</b>	50cm
<b>Mounting Option</b>	-
<b>Bracket Material</b>	Stainless steel
<b>Bolts and Screws</b>	Stainless steel

**PIOLED LIGHTING**

# OOBER IP65 LED Floodlight

**2 YEAR WARRANTY**

**3 SURGE PROTECTION**

**100% Satisfaction Guarantee**

**Free Shipping (US & Canada)**

**ErP CERTIFICATE**

**10 WATT**

**>0.9 PF**

**IP65**

**900 LM**

**120° BEAM ANGLE**

**50 CM CABLE**






Technical drawing of the LED light fixture showing side and front views with dimensions:

- Side view (left): Shows the profile of the fixture. The width of the base is labeled as 32 mm.
- Front view (right): Shows the square face of the fixture. The width of the base is labeled as 78 mm, and the height is labeled as 68 mm.

Input Current	44ma
Output Voltage	216
Humidity	-20-45°C
Frequency	50Hz
In Rush Current	500A
Output Current	40mA
THD	<15%
TA & TC	TA=90/TC=85
IES (Yes or No)	Yes
Regulatory Qualifications	
Class Rating	Class I
Energy Efficiency	A
Certification	CE, EMC, IEC60598
Accessories	
Optional accessories	Garden Spike and bracket for 10W to 20W - RF001
Packaging info	
Storage Temp	20-40°C
Carton Size (mm)	35.5*29.5*24.5
QTY/CTN	60
Net Weight	11,0
Gross Weight	12,7