



From Batch
2411 All Oober
Floodlights come
with a Stainless
Steel Bracket



Oober IP65 Floodlight

200W

Applications:

Residential and
Commercial Applications.

- Die-Cast Aluminium housing with dynamic fins providing as an efficient and effective heatsink.
- Driver on Board Technology allowing for a super compact, unobtrusive LED Floodlight.
- 50cm pre wired cable allowing for fast and easy installations.
- Pre-Installed Safety Clips protecting the LED Floodlights lens.
- 2835 Sanán LED Chips producing a CRI>83.
- 120° Wide Beam Angle allowing for maximum coverage and uniformity.
- 3kV Surge protection, designed for use specifically in the South African Market.


Product Performance

Wattage	200W
Colour Temperature & Stock Code	6000K F365
Operating Temperature	-30~45°C
Life Span/ LB Rating	25 000hrs
IP Rating	IP65
LED Driver Brand	DOB
Beam Angle	120°
Impact Protection Grade	IK06
Input Voltage	200V- 260V
Surge Protection	3kV
Power Factor	0.9
CRI	>83
Lumen Output	18 000 lumens
Lumen Efficiency	90lm/W
LED Chips	2835 Sanan
LED Chips Qty	280
Dimmable	Non-Dimmable
Dimmable Range	-
UGR	-
(Dali/Trailing/Leading)	-

Physical Characteristics

Weight (g)	2100
Housing Material	Die cast Aluminium
Product Dimensions (mm)	295*285*36
Cable Length	50cm
Mounting Option	-
Bracket Material	Stainless steel
Bolts and Screws	Stainless steel


Luminous Intensity Distribution Diagram



Packaging



Dimension Drawing



Technical Parameters

Input Current	859ma
Output Voltage	252
Humidity	-20-45°C
Frequency	50Hz
In Rush Current	2000A
Output Current	800mA
THD	<15%
TA & TC	TA=90/TC=85
IES (Yes or No)	Yes

Regulatory Qualifications

Class Rating	Class I
Energy Efficiency	A
Certification	CE, EMC, IEC60598
Accessories	

Optional accessories

-

Packaging info

Storage Temp	20-40°C
Carton Size (mm)	38.5*32*31.5
QTY/CTN	6
Net Weight	12,6
Gross Weight	14,5

E&OE

PioLED Lighting (Pty) Ltd | 031 701 5746 | info@pioledlighting.africa

www.pioledlighting.co.za