



Luka 3CCT Recessed Ceiling Light

12W

Applications:

Residential and
Commercial Applications.

- Backlit Round Recessed LED Ceiling Light, allowing for a cost effective LED Luminaire.
- 100lm/w 2835 SMD LED Chips, Available in 3CCT, with adjustable colour temperatures of 3000K, 4000K or 6000K.
- Instant On, environmentally friendly LED Ceiling Light containing no harmful chemicals or mercury.
- Opal Diffuser creating a soft uniform light distribution eliminating all visuals of the raw LEDs.
- The Luka ceiling light can be used in a wide range of indoor applications, such as living rooms, bedrooms, kitchens & offices.


Product Performance

Wattage	12W
Colour Temperature & Stock	i052 3CCT (3000K/4000K/6000K)
Operating Temperature	-20~40°C
Life Span/ LB Rating	L70B50
IP Rating	IP33
LED Driver	PioLED Driver
Beam Angle	120°
Input Voltage	200V- 240V
CRI	>80
Lumen Output	>1200@4000K
Lumen Efficiency (per watt)	>100lm/W
LED Chips	2835 SMD
LED Chips Qty	62
Dimmable	Non-Dimmable
Dimmable Range	-
(Dali/Trailing/Leading)	-
UGR	-
Physical Characteristics	
Weight (g)	110,6
Housing Material	PC
Product Dimensions (mm)	145*24.5
Cable length	12cm
Mounting Option	Recessed
Bracket Material	-
Bolts and Screws	-

Packaging



Dimension Drawing



Technical Parameters

Input Current	0.105A
Output Voltage	126V
Humidity	80%
Frequency	50-60Hz
In Rush Current	-
Output Current	0.085A
TA & TC	-
IES (Yes or No)	Yes

Regulatory Qualifications

Class Rating	Class I
Energy Efficiency	A
Certification	CE, CB, ERP, ROHS

Accessories

Optional accessories	i052a - Surface Mount Trim White for LUKA 12W
-----------------------------	---

Packaging info

Storage Temp	-20°C-80°C
Carton Size (mm)	47.3*39*32.2
QTY/CTN	60
Net Weight (kg)	7.2
Gross Weight (kg)	10.2

Surface Mount Case Available



E&OE

PioLED Lighting (Pty) Ltd | 031 701 5746 | info@pioledlighting.africa

www.pioledlighting.co.za