



Legend 3CCT Recessed Downlighter

35W


Applications:

Residential and Commercial Applications.

- Ultra Low Glare
 Downlight Light with
 a UGR<19, designed
 to reduce eye strain
 whilst creating a visually
 pleasing environment.</p>
- Available in a 3CCT selectable option, allowing customers to customize the lighting ambiance based on their room requirements.
- Quick and easy installation with its clips that quickly unspring and set the luminaire flush into the ceiling.
- Available for use in robust environments with its 185-270V Flicker Free, Lifud LED Power Supply with a warranty of 5 years.
- CRI>80 allowing for maximum versatility and an excellent choice when using for retail or commercial applications.

Product Performance	
Wattage	35W
Colour Temperature & Stock	iC063 3CCT (3000K/4000K/6000K)
Operating Temperature	-20~45°C
Life Span/ LB Rating	L80B20@50000
IP Rating	Front - IP44 Back - IP20
LED Driver	Lifud
Beam Angle	60°
Input Voltage	185V- 270V
CRI	>80
Power Factor	0.9
Surge Protection	1kV
Lumen Output	3500lm
Lumen Efficiency (per watt)	100lm/W
LED Chips	2835 Sanan
LED Chips Qty	9V 1W 112pcs
Dimmable	Optional Dimmable Driver i063Dim
Dimmable Range	-
(Dali/Trailing/Leading)	-
UGR	<19
Physical Characteristics	
Weight (g)	650
Housing Material	Aluminium
Product Dimensions (mm)	φ220*121mm
Cable length	49cm
Mounting Option	Recessed
Bracket Material	-
Bolts and Screws	-


Luminous Intensity Distribution Diagram



Packaging



Dimension Drawing



Technical Parameters	
Input Current	0.26A
Output Voltage	33-40V DC
Flicker Free (Y/N)	Yes
Humidity	-
Frequency	50-60Hz
In Rush Current	24A
Output Current	900mA
TA & TC	64.8°
IES (Yes or No)	Yes
Regulatory Qualifications	
Class Rating	Class I
Energy Efficiency	А
Certification	CE, EMC, IEC60598, ErP
Accessories	
Optional accessories	i063Dim - Legend 35W Dimmable Driver
Packaging info	
Storage Temp	-20°~45°
Carton Size (mm)	500*500*450mm
QTY/CTN	12
Net Weight (kg)	8.5
Gross Weight (kg)	9.5